

Articulated Dumper Range



AUSA	lb	cu yd	in	hp	in	in	in	in	lb	in
D 100 AHA / COMPACT	2,200	0.74	0.45	20.9	37.4/35.8	126.0	43.3/39.4	94.5/92.9	2,866	H-4x4
D 100 AHG	2,200	0.71	0.42	20.9	37.4	126.0	43.3	94.5	2,866	H-4x4
D 120 AHA	2,600	0.91	0.55	20.9	39.0	126.0	47.6	96.1	3,031	H-4x4
D 120 AHG	2,600	0.90	0.54	20.9	39.4	126.0	47.6	96.1	3,031	H-4x4
D 150 AHA	3,300	1.10	0.79	20.9	39.0	126.0	58.3	96.1	3,329	H-4x4
D 150 AHG	3,300	1.18	0.68	20.9	39.4	129.9	58.3	96.1	3,329	H-4x4
D 300 AHG	6,600	2.04	0.94	24.8	37.0	159.1	72.4	109.1	5,954	H-4x4
D 350 AHG	7,700	2.78	1.33	44	34.3	164.2	72.8	109.1	6,241	H-4x4
D 450 AHG	9,900	3.49	1.79	44	28.9	172.4	73.6	111.0	6,548	H-4x4
D 601 AHG	13,000	4.12	2.18	74.3	48.0	193.3	87.0	129.1	9,898	H-4x4
D 601 AP	13,000	4.16	2.47	74.3	16.5	183.9	87.0	129.1	9,900	P-4x4
D 601 APG	13,000	4.12	2.18	74.3	48.0	193.3	87.0	129.1	10,353	P-4x4
DR 601 AHG	13,000	4.12	2.18	74.3	48.0	193.3	87.0	142.1	10,648	H-4x4
D 1001 APG	22,000	5.10	2.42	74.3	49.6	197.6	94.9	143.3	11,431	P-4x4
DR 1001 AHG	22,000	5.10	2.42	74.3	49.6	197.6	94.9	143.3	11,133	H-4x4



AUSA US CORP
 9481 Industrial Center Dr, Unit 3,
 Ladson, SC 29456
 TEL: (843) 202 0387
ausa.us@ausa.com

AUSA Center: +34 93 874 7311 - ausa@ausa.com
 AUSA Spain: +34 91 669 00 06 ausa.madrid@ausa.com
 AUSA France: +33 (0) 4 68 54 38 97 - ausa.france@ausa.fr
 AUSA U.K.: +44 (0)7703 60 9009 - ausa.uk@ausa.com
 AUSA Central Europe: +49 2384 9415725 - info@ausa.de
 AUSA Brasil: +55 11 40146906 - ausa.brasil@ausa.com
 AUSA CHINA: +86 10 8598 7386 - ausa.china@ausa.com

Rigid Dumper Range



D 201 R

AUSA	lb	cu yd	in	hp	in	in	in	in	lb	in
D 201 RHS	4,400	1.63	0.91	24.8	22.4	118.9	68.9	101.6	4,188	H-4x4
D 201 RHGS	4,400	1.61	0.85	24.8	36.6	129.1	68.9	101.6	4,630	H-4x4



www.ausa.com



Forklift Range



AUSA	lb *	lb **	ft	hp	in	in	in	in	in	%	lb	
C 150 H	3,300	3,000	8.73	24.8	142.9	51.2	78.7	80.2	25%	5,950	H-4x2	
C 150 Hx4	3,300	3,000	8.73	24.8	142.9	51.2	80.3	80.2	25%	5,950	H-4x4	
C 251 H	5,500	5,000	10.82	41.8	172.6	59.8	84.2	96.8	25%	9,149	H-4x2	
C 251 Hx4	5,500	5,000	10.82	41.8	172.6	59.8	84.6	96.8	38%	9,414	H-4x4	
C 351 Hx4	7,700	7,000	10.82	41.8	178.4	70.1	86.2	105.1	30%	11,940	H-4x4	
C 400 Hx4	-	8,800	12.14	74.2	181.9	78.2	91.7	108.2	35%	16,314	H-4x4	
C 401 Hx4	-	8,800	12.14	74.2	181.5	79.1	92.5	108.2	35%	16,314	H-4x4	
C 500 Hx4	-	11,000	-	74.2	181.9	78.2	91.7	108.2	35%	17,010	H-4x4	
C 501 Hx4	-	11,000	12.14	74.2	181.5	79.1	92.5	108.2	35%	16,998	H-4x4	

* Load Capacity to 20" ** Load Capacity to 24"

Telehandler Range



AUSA	lb	ft	in	hp	%	in	in	in	in	lb	
T 144 H	3,000	13.1	66.22	24.8	25%	145.1	55.3	78.7	5,290	H-4x4	
T 204 H	4,400	13.8	81.57	42.9	42%	186.2	62.6	79.9	9,149	H-4x4x4	
T 235 H	5,000	16.4	92.83	42.9	44%	192.1	62.6	79.8	10,250	H-4x4x4	



The most complete range of compact machinery

Chassis: A = Articulated / R = Rigid · Transmission: H = Hydrostatic / P = Torque Converter · G = Rotating skip · S = Self-loading shovel